

サーミスタ抵抗値 YGC724M, YGCJ805M

冷媒吐出温／冷却水温／冷媒吸入温／膨張弁出口温サーミスタ

温度(℃)	抵抗値(KΩ)	温度(℃)	抵抗値(KΩ)	温度(℃)	抵抗値(KΩ)
-40	834.350	21	23.992	82	2.335
-39	775.545	22	22.914	83	2.262
-38	721.332	23	21.892	84	2.192
-37	671.321	24	20.921	85	2.125
-36	625.156	25	20.000	86	2.060
-35	582.514	26	19.125	87	1.998
-34	543.101	27	18.294	88	1.937
-33	506.651	28	17.504	89	1.879
-32	472.919	29	16.753	90	1.823
-31	441.685	30	16.039	91	1.769
-30	412.745	31	15.359	92	1.716
-29	385.916	32	14.713	93	1.666
-28	361.028	33	14.098	94	1.617
-27	337.929	34	13.512	95	1.570
-26	316.476	35	12.955	96	1.525
-25	296.543	36	12.423	97	1.481
-24	278.010	37	11.917	98	1.438
-23	260.769	38	11.434	99	1.398
-22	244.723	39	10.974	100	1.358
-21	229.780	40	10.535	101	1.320
-20	215.856	41	10.116	102	1.283
-19	202.876	42	9.717	103	1.247
-18	190.770	43	9.335	104	1.212
-17	179.472	44	8.971	105	1.179
-16	168.923	45	8.623	106	1.147
-15	159.069	46	8.291	107	1.115
-14	149.859	47	7.973	108	1.085
-13	141.247	48	7.670	109	1.056
-12	133.191	49	7.380	110	1.027
-11	125.650	50	7.102	111	1.000
-10	118.589	51	6.837	112	0.973
-9	111.973	52	6.583	113	0.947
-8	105.773	53	6.340	114	0.922
-7	99.958	54	6.107	115	0.898
-6	94.503	55	5.884	116	0.875
-5	89.384	56	5.671	117	0.852
-4	84.576	57	5.466	118	0.830
-3	80.060	58	5.271	119	0.809
-2	75.816	59	5.083	120	0.788
-1	71.825	60	4.903	121	0.768
0	68.072	61	4.730	122	0.749
1	64.540	62	4.565	123	0.730
2	61.215	63	4.406	124	0.712
3	58.083	64	4.253	125	0.694
4	55.133	65	4.107	126	0.677
5	52.352	66	3.967	127	0.660
6	49.729	67	3.832	128	0.644
7	47.256	68	3.702	129	0.628
8	44.922	69	3.578	130	0.613
9	42.718	70	3.458	131	0.598
10	40.637	71	3.343	132	0.584
11	38.671	72	3.233	133	0.570
12	36.813	73	3.127	134	0.556
13	35.056	74	3.025		
14	33.394	75	2.926		
15	31.822	76	2.832		
16	30.334	77	2.741		
17	28.925	78	2.653		
18	27.591	79	2.569		
19	26.326	80	2.488		
20	25.128	81	2.410		