

サーミスタ抵抗値 YCHJ80M-A

サーミスタ抵抗値

TH: 外気温 TH2: 冷媒熱交液温 TH3: 冷却水温1 TH4: 冷却水温2 TH5: エンジンルーム温
TH6: コンプレッサ温

温度(℃)	抵抗値(KΩ)
-40	1963.402
-39	1825.689
-38	1698.686
-37	1581.483
-36	1473.254
-35	1373.250
-34	1280.786
-33	1195.242
-32	1116.051
-31	1042.697
-30	974.709
-29	911.658
-28	853.151
-27	798.829
-26	748.364
-25	701.455
-24	657.829
-23	617.233
-22	579.436
-21	544.227
-20	511.410
-19	480.807
-18	452.254
-17	425.600
-16	400.707
-15	377.445
-14	355.698
-13	335.357
-12	316.322
-11	298.500
-10	281.807
-9	266.163
-8	251.496
-7	237.738
-6	224.828
-5	212.707
-4	201.323
-3	190.625
-2	180.569
-1	171.111
0	162.213
1	153.837
2	145.950
3	138.520
4	131.518
5	124.916
6	118.690
7	112.815
8	107.270
9	102.033
10	97.087

温度(℃)	抵抗値(KΩ)
11	92.413
12	87.994
13	83.815
14	79.862
15	76.120
16	72.578
17	69.224
18	66.046
19	63.034
20	60.179
21	57.471
22	54.902
23	52.465
24	50.150
25	47.953
26	45.865
27	43.881
28	41.996
29	40.203
30	38.498
31	36.875
32	35.331
33	33.861
34	32.461
35	31.128
36	29.857
37	28.646
38	27.492
39	26.391
40	25.340
41	24.388
42	23.382
43	22.468
44	21.596
45	20.763
46	19.967
47	19.206
48	18.478
49	17.783
50	17.117
51	16.481
52	15.871
53	15.288
54	14.730
55	14.195
56	13.683
57	13.192
58	12.722
59	12.271
60	11.838
61	11.423

温度(℃)	抵抗値(KΩ)
62	11.026
63	10.644
64	10.277
65	9.926
66	9.588
67	9.264
68	8.952
69	8.653
70	8.365
71	8.088
72	7.823
73	7.567
74	7.321
75	7.084
76	6.857
77	6.638
78	6.427
79	6.224
80	6.028
81	5.840
82	5.658
83	5.484
84	5.315
85	5.153
86	4.996
87	4.845
88	4.699
89	4.559
90	4.423
91	4.293
92	4.166
93	4.044
94	3.927
95	3.813
96	3.703
97	3.597
98	3.495
99	3.396
100	3.300
101	3.207
102	3.118
103	3.032
104	2.948
105	2.867
106	2.789
107	2.713
108	2.640
109	2.569
110	2.500
111	2.433
112	2.369

温度(℃)	抵抗値(KΩ)
113	2.307
114	2.246
115	2.188
116	2.131
117	2.076
118	2.022
119	1.971
120	1.921
121	1.872
122	1.825
123	1.779
124	1.735
125	1.692
126	1.650
127	1.610
128	1.570
129	1.532
130	1.495
131	1.459
132	1.424
133	1.390
134	1.357
135	1.325
136	1.294
137	1.264
138	1.234
139	1.206
140	1.178
141	1.151
142	1.125
143	1.099
144	1.074
145	1.050
146	1.027
147	1.004
148	0.982
149	0.960
150	0.939
151	0.918
152	0.898
153	0.879
154	0.860